

Dekster

Head Office
24 Fabriek Street, Kuils River, 7580
P.O.Box 131, Kuils River, 7579
South Africa

Tel: +27 (0)21 903 6042
Fax: +27 (0)86 611 0405
<http://www.dekster.co.za>
E-mail : info@dekster.co.za

DATA SHEET

DEKSTER 514 WATER BASED SANDING SEALER FOR WOOD

(Page 1 of 3)

V1-28/11/2014

DESCRIPTION

- Dekster 514 is a water based sealer for wood, designed for easy and safe application, to give protection from the elements and to bring out it's natural colour and beauty.

PROPERTIES

- Water Based Polyurethane
- Easy to apply
- No solvents, clean equipment with water
- Excellent UV resistance

RECOMMENDED AREAS FOR USE

- Counter tops
- Wooden decks
- Wooden garden furniture
- Wooden facias and balustrades

SURFACE PREPARATION

- Abrade the surface to be coated with 100grit sandpaper. If more than one coat is applied, lightly sand paper between coats when the previous coat is hard dry.

Dekster

Head Office
24 Fabriek Street, Kuils River, 7580
P.O.Box 131, Kuils River, 7579
South Africa

Tel: +27 (0)21 903 6042
Fax: +27 (0)86 611 0405
<http://www.dekster.co.za>
E-mail : info@dekster.co.za

DATA SHEET

DEKSTER 514 WATER BASED SANDING SEALER FOR WOOD

(Page 2 of 3)

V1-28/11/2014

APPLICATION

- Apply by sponge, brush or roller to achieve the desired effect.
-

CLEANING EQUIPMENT

- Clean all equipment immediately after use with water.
-

TOXICITY

- Dekster 514 is a relatively non-toxic and safe to use water based sealer. Refer to the relevant 16 point Material Safety Data Sheet.
-

HOW TO SPECIFY

- All wooden surfaces to be suitably prepared and coated with Dekster 514 Water Based Sealer, according to the manufacturer's instructions.
-

Dekster

Head Office
24 Fabriek Street, Kuils River, 7580
P.O.Box 131, Kuils River, 7579
South Africa

Tel: +27 (0)21 903 6042
Fax: +27 (0)86 611 0405
<http://www.dekster.co.za>
E-mail : info@dekster.co.za

DATA SHEET

DEKSTER 514 WATER BASED SANDING SEALER FOR WOOD

(Page 3 of 3)

V1-28/11/2014

TECHNICAL DATA

TYPE	: Urethane Acrylic
NUMBER OF COMPONENTS	: 1
COLOURS	: Dries Clear
FINISH	: Satin / Matt
NUMBER OF COATS	: 1 or 2
OVERCOATING TIME	: 2hrs – 4hrs
TOUCH DRY	: 2hrs
SOLIDS (By Volume)	: 40%
AVERAGE SPREAD RATE	: 10 -20m ² /l/coat
APPLICATION TEMPERATURE	: 5 to 40°C
SHELF LIFE	: 12 Months
PACKAGING	: 5 and 20 litres

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.