

Dekster

Head Office
24 Fabriek Street, Kuils River, 7580
P.O.Box 131, Kuils River, 7579
South Africa

Tel: +27 (0)21 903 6042
Fax: +27 (0)86 611 0405
<http://www.dekster.co.za>
E-mail : info@dekster.co.za

DATA SHEET

DEKSTER 604 BUILDERS MASTIC

(Page 1 of 2)

V1-17/07/2014

GENERAL DESCRIPTION

- Dekster 604 Builders Mastic is a water based general-purpose, flexible sealant that is used for caulking, grouting, jointing and embedding in building construction. It is easy to apply and compatible with most materials used in construction e.g. concrete, wood, brick, natural and artificial stone, glass, metal and sanitary-ware.

COLOURS

- Available in white or grey

SIZE

- 1lt, 5lt and 200 lt

USES / APPLICATIONS

- Caulking
- Grouting
- Jointing
- Embedding cornices
- Sealing between door / window frames and walls
- Holding down roof sheets
- Over paintable in one hour
- Highly flexible and Crack resistant
- Good adhesion to a variety of substrates
- Provides a smooth finish
- Non slump
- Water based, low odour and non toxic
- Suitable for interior and exterior applications
- Resistant to UV radiation, moisture and extreme temperature fluctuation

DEKSTER COATINGS (PTY) LTD REG NO. 2013/106812/07

Vat reg no:4120240140

Dekster

Head Office
24 Fabriek Street, Kuils River, 7580
P.O.Box 131, Kuils River, 7579
South Africa

Tel: +27 (0)21 903 6042
Fax: +27 (0)86 611 0405
<http://www.dekster.co.za>
E-mail : info@dekster.co.za

DATA SHEET

DEKSTER 604 BUILDERS MASTIC

(Page 2 of 2)

V1-17/07/214

OTHER INFORMATION

- Should not be used where high movement accommodation is needed
- Should not be used on oily or bituminous substrates, rubber or building material that may bleed oils, plasticizers or solvents
- It is not recommended for use in floor joints, as a glass sealant, or joints subject to continuous water immersion.
- When using Dekster Builders Mastic, do not expose to water or rain for at least 24 hours.
- Will not adhere to some plastics such as polyethylene, polypropylene and Teflon.

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.

DEKSTER COATINGS (PTY) LTD REG NO. 2013/106812/07

Vat reg no:4120240140