

# Dekster

Head Office  
24 Fabriek Street, Kuils River, 7580  
P.O.Box 131, Kuils River, 7579  
South Africa

Tel: +27 (0)21 903 6042  
Fax: +27 (0)86 611 0405  
<http://www.dekster.co.za>  
E-mail : [info@dekster.co.za](mailto:info@dekster.co.za)

## DATA SHEET

### DEKSTER 704 EPOXY THINNERS

(Page 1 of 1)

VI-28/11/2014

#### DESCRIPTION AND GENERAL USE

- Epoxy thinners is a mixture of different types of aromatic solvents and glycol acetates, which slows the evaporation rate.
- It can be used in various paint spraying applications. In both neat and blended form and in some brushing and roller applications.  
Suitable for all Dekster Epoxy Systems.

#### TECHNICAL DATA

<u>PROPERTY</u>	<u>TYPICAL</u>	<u>TEST METHOD</u>
APPEARANCE	Water White	Visual
FLASH POINT, TAG	23,0 °C	ASTM D56
COPPER CORROSION	Nil	ASTM D849
PURITY	Must match	ENE 01/99
ACIDITY	Nil	ASTM D847
DENSITY	0.83061	ASTM D1298

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users' responsibility to confirm the currency of product data sheets.

DEKSTER COATINGS (PTY) LTD REG NO. 2013/106812/07

Vat reg no:4120240140